

RECEIVED  
CENTRAL FAX CENTER

SEP 16 2008

Amendments to the Claims:

1. (Previously amended) A method of selecting a plurality of frequency bands for use in a desired wireless communication from among a plurality of frequency bands available to be used for the desired wireless communication, comprising:

passively monitoring the plurality of frequency bands to determine interference information for each of the frequency bands;

summing the interference information of said each of the frequency bands to produce a signal quality indication; and

selecting the plurality of frequency bands for the desired wireless communication in response to the signal quality indication.

2. (Previously amended) The method of Claim 1, wherein said passive monitoring step includes monitoring communication quality associated with the plurality of frequency bands.

3. (Previously amended) The method of Claim 1, wherein said passive monitoring step includes monitoring interference associated with the plurality of frequency bands.

4. (Canceled)

5. (Previously amended) The method of Claim 1, wherein said plurality of frequency bands are narrow frequency bands comprising a wide frequency band.

6. (Previously amended) The method of Claim 5, wherein the wide frequency band is an IEEE 802.11b band.

7. (Previously amended) The method of Claim 1, wherein at least one frequency band of the plurality of frequency bands is a Bluetooth 2.0 band.

TI-31670, Page 2

8. (Previously amended) The method of Claim 1, wherein said passive monitoring step includes each of two wireless communication stations passively monitoring at least some of said plurality of frequency bands.

9. (Original) The method of Claim 8, including one of said wireless communication stations communicating with the other of said wireless communication stations regarding results of said passive monitoring.

10. (Original) The method of Claim 1, wherein said passive monitoring step includes passively monitoring a group of the available frequency bands, and tuning a filter to each of said group of available frequency bands.

11. (Previously amended) The method of Claim 1, wherein the plurality of frequency bands includes a frequency band associated with microwave oven interference.

12. (Previously amended) The method of Claim 1, wherein said selecting step includes the wireless communication station selecting the plurality of frequency bands for the desired wireless communication and informing another wireless communication station of the selected frequency bands.

13. (Currently amended) A wireless communication station, comprising:

an antenna for use in wireless communications;

a band selection controller coupled to said antenna for selecting ~~a frequency band for use in a desired wireless communication from among~~ a plurality of frequency bands available to be used for the desired wireless communication;

said band selection controller operable for passively monitoring ~~at least one of the available~~ each frequency band of the plurality of frequency bands to determine whether the at least one frequency band is acceptable for the desired wireless communication respective interference information for said each frequency band;

said band selection controller operable for ~~selecting a first bandwidth for a first application and for selecting a second bandwidth different from the first bandwidth for a second application of the at least one of the available frequency bands~~ summing the respective interference information of said each frequency band to produce a signal quality indication; and

said band selection controller further operable for selecting the ~~at least one frequency band for the desired wireless communication if the at least one frequency band is determined to be acceptable~~ plurality of frequency bands for the desired wireless communication in response to the signal quality indication.

14. (Currently amended) The wireless communication station of Claim 13, wherein said band selection controller includes an interference monitor for monitoring interference associated with ~~the at least one~~ said each frequency band.

15. (Original) The wireless communication station of Claim 14, wherein said interference monitor includes an RSSI measurement apparatus.

16. (Original) The wireless communication station of Claim 13, including a wireless communications interface coupled between said antenna and said band selection controller, said wireless communications interface cooperable with said band selection controller and said antenna for communicating to another wireless communication station information indicative of a result of said passive monitoring operation.

17. (Currently amended) The wireless communication station of Claim 13, including a wireless communications interface coupled between said antenna and said band selection controller, said wireless communications interface cooperable with said antenna for receiving and providing to said band selection controller a passive monitoring result which is associated with ~~the at least one~~ said each frequency band and which has been obtained and transmitted by another wireless communication station, said band selection controller operable for determining whether ~~the at least one~~ said each frequency band is acceptable for the desired wireless

communication in response to said result received from said another wireless communication station.

18. (Currently amended) The wireless communication station of Claim 13, wherein said band selection controller includes a filter coupled to said antenna for tuning to ~~each of a group of the available frequency bands~~ said each frequency band, said band selection controller including a passive monitor coupled to said filter for passively monitoring ~~each of said group of available frequency bands~~ said each frequency band.

19. (Original) The wireless communication station of Claim 13, including a wireless communications interface coupled to said antenna for interfacing between said antenna and a communications application, said band selection controller including a portion of said wireless communications interface.

20. (Currently amended) The wireless communication station of Claim 19, wherein said portion of said wireless communications interface includes a filter for tuning to ~~the at least one frequency band~~ said each frequency band and an RSSI measurement apparatus coupled to said filter for providing an RSSI measurement with respect to ~~the at least one~~ said each frequency band.

21. (Original) The wireless communication station of Claim 13, provided as one of a Bluetooth station and an IEEE 802.11b station.

22-32. (Cancelled)